

Overview


HP Z2 Mini G5 Workstation



Front-Side View

1. Power button
2. 2 Type-A SuperSpeed USB 10Gbps signaling rate port (1 supports charging)
3. 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (charging supported)
4. Universal audio jack

Overview



Rear View

1. HDD Activity LED
2. Power connector
3. 2 DisplayPort™ 1.4³
1 DisplayPort™ (optional)^{1,3}
4. Standard cable lock slot
5. Cover release latch
6. 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (charging supported) (optional)²
7. Flex IO modules, choice of:
Dual Type-A SuperSpeed USB 5Gbps signaling rate port, serial port²
8. Flex IO modules, choice of:
VGA, HDMI 2.0b, DisplayPort™ 1.4³, Dual Type-A SuperSpeed USB 5Gbps signaling rate port, serial port, 2nd 1GbE LAN, Type-C® SuperSpeed USB 10Gbps signaling rate port (Alt Mode), Thunderbolt™ 3, 2.5GbE LAN²
9. RJ-45
10. 2 Type-A SuperSpeed USB 10Gbps signaling rate port

¹Available only when a discrete graphic card is installed.

²Available on selected configurations only.

³All DisplayPort™ support DP1.4/HBR2 when video output is via Intel Graphics.

Overview

Form Factor

Mini

Operating Systems

Preinstalled:

- Windows 10 Pro 64¹
- Windows 10 Pro 64 High End¹
- Windows 10 Pro 64 Workstation Plus¹
- Windows 10 Home 64 Plus¹
- Windows 10 Home 64 Advanced¹¹
- Linux-ready²

¹Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply, and additional requirements may apply over time for updates. See <http://www.windows.com>

² For detailed Linux[®] OS/hardware support information, see: http://www.hp.com/support/linux_hardware_matrix

NOTE: In accordance with Microsoft's support policy, HP does not support the Windows[®] 7 operating system on products configured with Intel[®] 7th Generation and forward processors.

Processors*

Name	Cores	Clock Speed (GHz)	Cache (MB)	Memory Speed (MT/s)	Hyper-Threading	Integrated Graphics	Intel [®] Turbo Boost Technology ²	Featuring Intel [®] vPro [™] Technology ³	16GB Intel [®] Optane [™] memory	TDP (W)
Intel [®] Core [™] i9-10900K Processor ⁵	10	3.7	20	2933	Y	Intel [®] UHD Graphics 630	5.2	Y	Y	125
Intel [®] Core [™] i9-10900 Processor	10	2.8	20	2933	Y	Intel [®] UHD Graphics 630	5.1	Y	Y	65
Intel [®] Core [™] i9-10900F Processor ⁴	10	2.8	20	2933	Y	N/A	5.1	N/A	Y	65
Intel [®] Core [™] i7-10700K Processor ⁵	8	3.8	16	2933	Y	Intel [®] UHD Graphics 630	5.1	Y	Y	125
Intel [®] Core [™] i7-10700 processor	8	2.9	16	2933	Y	Intel [®] UHD Graphics 630	4.8	Y	Y	65
Intel [®] Core [™] i5-10600K processor ⁵	6	4.1	12	2666	Y	Intel [®] UHD Graphics 630	4.8	Y	Y	125
Intel [®] Core [™] i5-10600 processor	6	3.3	12	2666	Y	Intel [®] UHD Graphics 630	4.8	Y	Y	65
Intel [®] Core [™] i5-10500 processor	6	3.1	12	2666	Y	Intel [®] UHD Graphics 630	4.5	Y	Y	65
Intel [®] Core [™] i5-10400 processor	6	2.9	12	2666	Y	Intel [®] UHD Graphics 630	4.3	N/A	Y	65
Intel [®] Core [™] i5-10400F Processor ⁴	6	2.9	12	2666	Y	N/A	4.3	N/A	Y	65
Intel [®] Core [™] i3-10320 processor ⁴	4	3.8	8	2666	Y	Intel [®] UHD Graphics 630	4.6	N/A	Y	65
Intel [®] Core [™] i3-10300 processor ⁴	4	3.7	8	2666	Y	Intel [®] UHD Graphics 630	4.4	N/A	Y	65
Intel [®] Core [™] i3-10100 processor	4	3.60	6	2666	Y	Intel [®] UHD Graphics 630	4.3	N/A	Y	65
Intel [®] Xeon [®] W-1290P processor ⁵	10	3.7	20	2933	Y	Intel [®] UHD Graphics P630	5.2	Y	Y	125

Overview

Intel® Xeon® W-1290 processor ⁴	10	3.2	20	2933	Y	Intel® UHD Graphics P630	5.1	Y	Y	80
Intel® Xeon® W-1270P processor ^{4,5}	8	3.8	16	2933	Y	Intel® UHD Graphics P630	5.1	Y	Y	125
Intel® Xeon® W-1270 processor	8	3.4	16	2933	Y	Intel® UHD Graphics P630	5.0	Y	Y	80
Intel® Xeon® W-1250P processor ⁵	6	4.1	12	2666	Y	Intel® UHD Graphics P630	4.8	Y	Y	125
Intel® Xeon® W-1250 processor	6	3.3	12	2666	Y	Intel® UHD Graphics P630	4.7	Y	Y	80

¹Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

²The specifications shown in the Intel® Turbo Boost Technology column represent the maximum turbo frequency with one core active. Turbo boost stepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

³ For full Intel® vPro™ functionality, Windows, a vPro™ supported processor, vPro™ enabled Q370 chipset or higher and vPro™ enabled WLAN card are required. Some functionality, such as Intel Active management technology and Intel Virtualization technology, requires additional 3rd party software in order to run. Availability of future "virtual appliances" applications for Intel vPro™ technology is dependent on 3rd party software providers. Compatibility of this generation of Intel vPro™ technology-based hardware with future "virtual appliances" is yet to be determined.

⁴Available in Q4, 2020

⁵Configurable TDP-down 95W

Convertibility	Z2 Mini G5 can either be placed on a flat surface or mounted behind a display or under a desk. (Mounting sold separately)
Expansion Slots (see system board section for more details)	Custom PCIe Gen3 x16 for factory-integrated graphics module – if anything, should put JUST the M.2 slot here since that is a true “expansion slot”
Front I/O	
Side I/O	2 Type-A SuperSpeed USB 10Gbps signaling rate port (upper port supports charging), 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (charging supported), 1 Universal audio combo
Rear I/O	2 DisplayPort™ 1.4 ¹ , 1 RJ-45 port, 2 Type-A SuperSpeed USB 10Gbps signaling rate port
	Optional: 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (optional, supports charging), 1 DisplayPort™ 1.4 ¹ , 2 Flex IO modules
On-board RAID Support	NVMe RAID 0 Striped Array NVMe RAID 1 Mirrored Array
Chassis Dimensions (H x W x D)	H: 2.28" [58mm] (Standard desktop orientation) W: 8.5" [216mm] D: 8.5" [216mm]
Packaged Dimensions	H: 11.73" (298mm) W: 6.69" (170mm) D: 19.65" (499mm)

Overview

Rack Dimensions	5U
Weight	Exact weights depend upon configuration Minimum: 2.1kg (4.6lbs.) Maximum: 2.42kg (5.3lbs.)
Temperature	Operating: 5° to 35° C (40° to 95° F) Above 1524 m (5,000 feet) altitude, the maximum operating temperature is reduced by 1° C (1.8° F) for every 305 m (1,000 feet) increase in elevation Non-operating: -40° to 60° C (-40° to 140° F) Maximum rate of change: 10°C/hr
Humidity	Operating: 10% to 85% RH, non-condensing, 35° C maximum wet bulb Non-operating: 10% to 90% RH, non-condensing, 35° C maximum wet bulb
Maximum Altitude (non-pressurized)	Operating (with Rotational Hard Drives): 3,048 m (10,000 feet) Operating (with only Solid-State Drives): 5,000 m (16,404 feet) Non-operating: 12,192 m (40,000 feet) Maximum operating temperature is reduced as altitude increases. See Temperature for details.
Power Supply	Choice of: 180W 89% Average Efficiency. 280W 89% Average Efficiency. NOTES: Customers placing their system in an enclosure should design their solution to accommodate the size of the external power supply for the Z2 Mini G5
Workstation ISV Certifications	See the latest list of certifications at http://www.hp.com/united-states/campaigns/workstations/partnerships.html
Chipset	Intel® W480 chipset
Memory	2 SODIMM slots, supporting up to 64GB ECC/non-ECC, DDR4 2933 MT/s, speed depending on the CPU selection. ¹ All DisplayPort™ support DP1.4/HBR2 when video output is via Intel Graphics. Discrete graphics support DP1.4 / HBR3.

Supported Components

Processors	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
10th Generation Intel Core Processors¹				
Intel® Core™ i9 10900K Processor	Y	N		3
Intel® Core™ i9 10900 Processor	Y	N		
Intel® Core™ i9 10900F Processor	Y	N		1
Intel® Core™ i7 10700K Processor	Y	N		3
Intel® Core™ i7 10700 processor	Y	N		
Intel® Core™ i5 10600K processor	Y	N		3
Intel® Core™ i5 10600 processor	Y	N		
Intel® Core™ i5 10500 processor	Y	N		
Intel® Core™ i5 10400 processor	Y	N		
Intel® Core™ i9 10400F Processor	Y	N		1
Intel® Core™ i3 10320 processor	Y	N		2
Intel® Core™ i3 10300 processor	Y	N		2
Intel® Core™ i3 10100 processor	Y	N		
Intel Xeon W Processors				
Intel® Xeon® W-1290P processor	Y	N		3
Intel® Xeon® W-1290 processor	Y	N		2
Intel® Xeon® W-1270P processor	Y	N		2,3
Intel® Xeon® W-1270 processor	Y	N		
Intel® Xeon® W-1250P processor	Y	N		3
Intel® Xeon® W-1250 processor	Y	N		
¹ These processors support only non-ECC memory				
NOTE 1: No integrated graphics. A discrete graphics card must be purchased at the same time. Available in Q4, 2020				
NOTE 2: Available in Q4, 2020				
NOTE 3: TDP configured down to 95W.				

Storage / Hard Drives*	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
SATA Hard Drives				
500GB SATA 7200 rpm 6Gb/s SFF HDD (2.5")	Y	Y	T0K73AA	
1TB SATA 7200 rpm 6Gb/s SFF HDD (2.5")	Y	Y	T0K74AA/AT	
2 TB SATA 5400 rpm SFF HDD (2.5")	Y	N		
500GB SATA 7.2K SED SFF HDD	Y	Y	D8N29AA	
SATA Solid State Drives				
HP 256GB SATA 6Gb/s SSD	Y	Y		
HP 2TB SATA SSD PROMO			Y6P08AT	
PCIe Solid State Drives				
HP ZTurbo 1TB TLC Z2 G5 Mini SSD Kit	Y	Y	141L4AA/AT	
HP ZTurbo 256GB SED Z2 G5 Mini SSD Kit	Y	Y	141L6AA/AT	
HP ZTurbo 256GB TLC Z2 G5 Mini SSD Kit	Y	Y	141L9AA/AT	
HP ZTurbo 2TB TLC Z2 G5 Mini SSD Kit	Y	Y	141M0AA/AT	

Supported Components

HP ZTurbo 2TB TLC Z2 G5 TWR/SFF SSD Kit	Y	Y	141M1AA/AT
HP ZTurbo 512GB SED Z2 G5 Mini SSD Kit	Y	Y	141M2AA/AT
HP ZTurbo 512GB SED Z2 G5 TWR/SFF SSD Kit	Y	Y	141M3AA/AT
HP ZTurbo 512GB TLC Z2 G5 Mini SSD Kit	Y	Y	141M4AA/AT
HP ZTurbo 512GB TLC Z2 G5 TWR/SFF SSD Kit	Y	Y	141M5AA/AT

NOTE1: SATA hardware-assisted RAID is not supported on Linux® systems. The Linux® kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-assisted RAID. All drives must be identical in type and capacity. Boot volume/RAID array must be less than 2 TB

NOTE2: 125W CPU SKU is not supported to install the SATA 2.5in HDD or SSD.

NOTE3: 65W CPU and MXM GFX card SKU is not supported to install the SATA 2.5in HDD or SSD.

*For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Graphics Cable Adapters				
HP DisplayPort To HDMI True 4k Adapter	Y	Y	2JA63AA	
HP DisplayPort To DVI-D Adapter	Y	Y	FH973AA	
HP DisplayPort To VGA Adapter	Y	Y	AS615AA	
HP USB-C to DisplayPort Adapter	Y	Y	4SH08AA	
HP USB-C to HDMI Adapter	Y	Y	4SH07AA	
HP USB-C to VGA Adapter	Y	Y	4SH06AA	
Entry 3D				
AMD Radeon™ Pro WX 3200 4GB MXM Graphics	Y	N		
NVIDIA® Quadro® P620 4GB MXM Graphics	Y	N		1
Mid-range 3D				
NVIDIA® Quadro® T1000 4GB MXM Graphics	Y			
NVIDIA® Quadro® T2000 4GB MXM Graphics	Y			
NVIDIA® Quadro® RTX 3000 6GB MXM Graphics	Y	N		2
NOTE 1: Available in Q4, 2020				
NOTE 2: Available in Q1, 2021				

Memory

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 4GB (1x4GB) DDR4-3200 nECC SO DIMM	Y			
HP 8GB (2x4GB) DDR4-3200 nECC SO DIMM	Y			
HP 8GB (1x8GB) DDR4-3200 nECC SO DIMM	Y			
HP 8GB (1x8GB) DDR4-3200 ECC SO DIMM	Y			
HP 16GB (2x8GB) DDR4-3200 nECC SO DIMM	Y			
HP 16GB (2x8GB) DDR4-3200 ECC SO DIMM	Y			
HP 16GB (1x16GB) DDR4-3200 nECC SO DIMM	Y			
HP 16GB (1x16GB) DDR4-3200 ECC SO DIMM	Y			

Supported Components

HP 32GB (2x16GB) DDR4-3200 nECC SO DIMM	Y	
HP 32GB (2x16GB) DDR4-3200 ECC SO DIMM	Y	
HP 32GB (1x32GB) DDR4-3200 nECC SO DIMM	Y	
HP 32GB (1x32GB) DDR4-3200 ECC SO DIMM	Y	
HP 64GB (2x32GB) DDR4-3200 nECC SO DIMM	Y	
HP 64GB (2x32GB) DDR4-3200 ECC SO DIMM	Y	
AMO		
HP 4GB (1x4GB) DDR4-3200 nECC SO DIMM	N	141J0AA/AT
HP 8GB (1x8GB) DDR4-3200 nECC SO DIMM	N	141J5AA/AT
HP 8GB (1x8GB) DDR4-3200 ECC SO DIMM	N	141J2AA/AT
HP 16GB (1x16GB) DDR4-3200 nECC SO DIMM	N	141H5AA/AT
HP 16GB (1x16GB) DDR4-3200 ECC SO DIMM	N	141H4AA/AT
HP 32GB (1x32GB) DDR4-3200 nECC SO DIMM	N	141H8AA/AT
HP 32GB (1x32GB) DDR4-3200 ECC SO DIMM	N	141H6AA/AT

NOTES: The CPUs determine the speed at which the memory is clocked. If a 2666 MHz capable CPU is used in the system, the maximum speed the memory will run at is 2666 MHz regardless of the specified speed of the memory.

Intel® Xeon® W processors can support either ECC or non-ECC memory; Intel® Core™ i3/i5/i7 processors only support non-ECC memory.

Two channels of DDR4 memory are supported. To realize full performance at least one DIMM must be inserted into each channel.

Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number
HP Slim Tray Optical Drives			
HP External Ultra-Slim DVD-RW Drive	N	Y	Y3T76AA

Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number
Integrated Intel® I219LM PCIe GbE Controller (Intel® vPro™ with Intel AMT 12.0)	Y	N	
Intel Wi-Fi 6 AX201 (2x2) and Bluetooth 5 combo	Y	N	
HP 1GbE LAN Flex Port 2020	Y	Y	141J6AA/AT
HP 2.5GbE LAN Flex Port Z2 Mini	Y	Y	169K0AA/AT

NOTE 1: The integrated network connection is required to support Intel® vPro™ Technology.

NOTE 2: If AMT is provisioned, then network teaming with the integrated LAN port is not possible.

NOTE 3: "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

Supported Components

Racking and Physical Security	Factory Configured	Option Kit	Option Kit Part Number
HP Keyed Cable Lock 10mm	N	Y	T1A62AA
Z2 Mini ePSU Sleeve	N	Y	3RW68AA
HP Z2 Mini Vertical Stand	N	Y	3RW66AA
HP Z2 Mini VESA Sleeve	N	Y	Y7B61AA
HP Business PC Security Lock v3 Kit	N	Y	3XJ17AA
HP Z2 Mini Rack Tray Support Kit	N	Y	1A4W4AA
HP Z2 Mini and TWR/Z4/Z6 G4 Depth Adjustable Fixed Rail Rack Kit	N	Y	2HW42AA/AT
Z2 G5 Mini HDD Carrier Cage	Y	Y	1X5Q2AA/AT

Input Devices	Factory Configured	Option Kit	Option Kit Part Number
HP Premium Wireless Keyboard	Y	Y	Z9N41AA/AT
HP USB 320K Keyboard	Y	Y	9SR37AA
HP USB Business Slim Wired Smartcard CCID Keyboard	Y	N	
HP Wireless Business Slim Keyboard and Mouse	Y	Y	
HP USB Premium Wired Keyboard	Y	Y	Z9N40AT
HP 320M Wired Mouse	Y	Y	9VA80AA
HP USB Premium Mouse	Y	Y	1JR32AA
HP Wireless Premium Mouse	Y	Y	1JR31AA
3Dconnexion CAD Mouse	N	Y	M5C35AA
HP Wired Desktop 320MK Mouse and Keyboard	N	Y	9SR36AA

Other Hardware	Factory Configured	Option Kit	Option Kit Part Number
HP Z2 Power Cord Kit	Y	Y	1N1D5AA
HP DP Flex Port 2020	Y	Y	141J7AA/AT
HP Dual USB-A 3.2 Gen1 Flex Port 2020	Y	Y	141J8AA/AT
HP Dual USB-A 3.2 Gen1 Flex Port 2020 Mini	Y	Y	141J9AA/AT
HP USB-C® 3.2 Gen2 Alt Flex Port 2020	Y	Y	141K6AA/AT
HP HDMI Flex Port 2020	Y	Y	141K1AA/AT
HP VGA Flex Port 2020	Y	Y	141K7AA/AT
HP Mini Serial Upper Flex Port 2020 Mini	Y	Y	141K2AA/AT
HP Thunderbolt™ 3 Flex Port 2020 Mini	Y	Y	141K4AA/AT

Software	Factory Configured	Option Kit	Support Notes
HP Performance Advisor	Y	N	1
HP PC Hardware Diagnostics UEFI (Windows OS only)	Y	N	2
HP PC Hardware Diagnostics Windows	Y	N	

Supported Components

ZCentral Remote Boost	Y	N
HP Sure Sense	Y	N
HP Notifications	Y	N
HP Desktop Support Utility	Y	N
HP Documentation	Y	N
HP Image Assistant	N	N
HP Support Assistant	N	N

NOTE 1: Supports and preinstalled with Windows 10 only. Also available as a free download from <http://www.hp.com/go/performanceadvisor>

NOTE 2: Windows OS only

Operating Systems

Windows 10 Pro 64
 Windows 10 Pro 64 High End
 Windows 10 Pro 64 Workstation Plus
 Windows 10 Home 64 Plus
 Windows 10 Home 64 Advanced
 Linux Ready

NOTE: For detailed QS/hardware support information for Linux, see: http://www.hp.com/support/linux_hardware_matrix

HP BIOS

Key features of the HP BIOS include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP Z2 G5 Workstation into the enterprise, such as PXE, remote recovery, remote configuration, remote control, and BIOS (F10) Setup support for 15 languages.
- Network firmware updates – Update your BIOS via the cloud or standardize on a BIOS version hosted on an Enterprise network.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- UEFI specification version 2.7
- Absolute Persistence agent – For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Workstation computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Workstation computers, including BIOS updates from within Windows (HP Firmware Update and Recovery), HP Client Manager, and fail-safe recovery. In addition, the HP BIOS Configuration Utility enables replication of BIOS settings within Windows while the Replicated Setup feature provides the same capability within BIOS (F10) Setup. The BIOS Configuration Utility is available from the HP support website.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery.

Additional HP BIOS Features:

Supported Components

- Power-On password – Helps prevent an unauthorized user from powering on the system.
- Administrator password – Also known as the BIOS Setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS cannot be updated and changes cannot be made to BIOS settings using BIOS Setup or under the OS.
- S4/S5 Maximum Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 0.5W in S4/S5 (when turned off). When S4/S5 Maximum Power Savings feature is enabled below features are turned off:
 - -Power to expansion connectors / slots
 - -Wake events other than power buttons (such as wake on LAN)
 - -USB charging ports

HP Sure Start Gen6 Start

- BIOS Integrity checking – Sure Start protection ensures that only trusted BIOS code is executed and not rootkits, viruses and malware. Verification is done upon boot up, shutdown and while the system is on.
- Sure Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability. Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability.
- Protecting beyond BIOS – Integrity checking and repair is extended to other data that should be protected such as network configuration parameters, platform specific information (i.e. system IDs), secure boot credentials, and other code the system needs to boot.
- Audit enabled – System Audit via Sure Start Event Logs capture data such as incident, repair date and time for troubleshooting and investigating.

SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

BIOS

HP BIOSphere Gen6¹⁰

BIOS Update via Network

HP Secure Erase¹¹

Absolute Persistence Module¹²

Pre-boot Authentication

HP Wake on WLAN

HP DriveLock & Automatic DriveLock¹³

Software

HP Support Assistant

HP Image Assistant

HP Desktop Support Utility

HP Documentation

HP Notifications

HP PC Hardware Diagnostics UEFI

HP PC Hardware Diagnostics Windows

HP Performance Advisor³

ZCentral Remote Boost¹⁴

Supported Components

Manageability Features

HP Driver Packs¹
HP System Software Manager (SSM)
HP BIOS Config Utility (BCU)
HP Manageability Integration Kit Gen4²

Client Security Software

HP Client Security Manager Gen6⁴
HP Device Access Manager
HP Power On Authentication
Microsoft Defender⁵

Security Management

HP Sure Click⁹
HP Sure Start Gen6⁶
HP Sure Run Gen3⁷
HP Sure Sense¹⁵
HP Sure Recover Gen3⁸

1. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
2. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>
3. HP Performance Advisor Software - HP Performance Advisor is ready and waiting to help you get the most out of your HP Workstation from day one—and every day after. Learn more or download at: <https://www8.hp.com/us/en/workstations/performance-advisor.html>
4. HP Client Security Manager Gen6 requires Windows and is available on select HP Pro, Elite and Workstation PCs. See product specifications for details..
5. Microsoft Defender Opt in and internet connection required for updates.
6. HP Sure Start Gen6 is available on HP Workstation products equipped with Intel® 8th generation processors or later
7. HP Sure Run is available on HP Workstation products equipped with 8th generation Intel® or AMD® processors.
8. HP Sure Recover Gen3: See product specifications for availability. Requires an open, wired network connection. Not available on platforms with multiple internal storage drives. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi is only available on PC's with Intel Wi-Fi Module.
9. HP Sure Click requires Windows 10 Pro or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.
10. HP BIOSphere Gen6 is available on select HP Pro, Elite and Workstation PCs. See product specifications for details. Features may vary depending on the platform and configurations.
11. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
12. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
13. Storage Drivelock does not work with Self Encrypting or Optane based storage.
14. HP Z Central Remote Boost Software does not come preinstalled on Z Workstations but can be downloaded and run on all Z desktop and laptops without license purchase. With non-Z sender devices, purchase of perpetual individual license or perpetual floating license per simultaneously executing versions and purchase of ZCentral Remote Boost Software Support is required. RGS requires Windows, RHEL (7 or 8), UBUNTU 18.04 LTS, or HP ThinPro 7 operating systems. MacOS (10.13 or newer) operating system is only supported on the receiver side. Requires network access. The software is available for download at hp.com/ZCentralRemoteBoost.
15. HP Sure Sense requires Windows 10 Pro or Enterprise. See product specifications for availability.

System Technical Specifications

System Board

System Board Form Factor	202.2 x 198.5 mm (7.96 x 7.815 inch)	
Processor Socket	Single LGA-1200	
CPU Bus Speed	DMI	
Chipset	Intel® PCH W480	
Super I/O Controller	Nuvoton SIO18	
Memory Expansion Slots	2 DDR4 memory slots	
Memory Type Supported	DDR4, SODIMM ECC & non-ECC	
Memory Modes	Non-Interleaved for single channel. Interleaved when both channels are populated.	
Memory Speed Supported	2933MT/s DDR4	
Memory Protection	ECC available on data	
Maximum Memory	64GB	
Memory Configuration (Supported)	4GB, 8GB 16GB and 32GB non-ECC and 8GB, 16GB and 32GB ECC SO DIMMs are supported. ECC and non-ECC memory DIMMs cannot be mixed in the same system	
PCI Express Connectors	<ul style="list-style-type: none"> • 1 MXM PCI Express Gen3 slot x1 • 2 M.2 Storage (PCIe Gen3 x4) • 1 M.2 WLAN (PCIe Gen3 x1+ Intel CNVi) 	
Supported Drive Interfaces	SATA	Integrated (1) Serial ATA interfaces (6Gb/s SATA).
	Network Controller	Integrated Ethernet PHY Connection I219LM. Management capabilities: WOL, PXE 2.1 and AMT 12
	Serial	1 rear port (requires optional Serial Port Adapter Kit)
	HD Integrated Audio	Yes
USB Connector(s)	Front	2 Type-A SuperSpeed USB 10Gbps signaling rate port (1 charge supports up to 5V/2.1A); 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (charge supports up to 5V/3A)
	Rear	2 Type-A SuperSpeed USB 10Gbps signaling rate port; 1 Type-C® SuperSpeed USB 10Gbps signaling rate port (optional); 1 Type-C® SuperSpeed USB 10Gbps signaling rate Alt mode port (optional via Flex)
	Internal	2 Type-A SuperSpeed USB 5Gbps signaling rate port
HD Integrated Audio	Yes	
Flash ROM	Yes	
CPU Fan Header	Yes	
Memory Fan Header	None	
Chassis Fan Header	None	
Front PCI Fan Header	1 GPU Fan (most)	

System Technical Specifications

Front Control Panel/Speaker Header	Yes
CMOS Battery Holder - Lithium	Yes
Integrated Trusted Platform Module	Integrated TPM 2.0 Convertible to FIPS 140-2 Certified mode through firmware v7.85 The TPM module disabled where restricted by law, i.e. Russia.
Power Supply Headers	DC Jack for adapter
Power Switch, Power LED & Hard Drive LED Header	Yes
Clear Password Jumper	None
Keyboard/Mouse	USB
Operating Voltage Range	90–269 VAC
Rated Voltage Range	100–240 VAC
Rated Line Frequency	50–60 Hz
Operating Line Frequency Range	47–66 Hz
Rated Input Current	6A@100-240V
Heat Dissipation	Typical: 444 btu/hr (112 kcal/hr) Maximum: 1484 btu/hr (374 kcal/hr)
ENERGY STAR® certified (Config Dependent)	Yes
CECP Compliant @ 220V	Yes
FEMP Standby Power Compliant	Yes, with Wake-on-LAN disabled: <2W in S5- Power Off
Built-in Self Test (BIST) LED	No
Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)	Yes

System Configurations

Z2 Mini G5 Configuration #1 ENERGY STAR CERTIFIED	Processor Info	CPU I Core i5-10400 2.9GHz 6C65W
	Memory Info	8GB (1x 8GB) 2666 MHz DDR4 non-ECC
	Graphics Info	Intel® UHD Integrated Graphics 630
	Disks/Optical/Floppy	1x SATA 1TB 7.2k rpm
	Power Supply	180W

Energy Consumption		115 VAC	230 VAC	100 VAC
--------------------	--	---------	---------	---------

System Technical Specifications

(Watts)	LAN Enabled		LAN Disabled		LAN Enabled		LAN Disabled	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	7.38		8.76		7.03			
Windows short Idle (S0)	10.74		12.02		9.96			
Windows Busy Typ (S0)	90.37		99.52		88.23			
Windows Busy Max (S0)	95.11		102.78		93.86			
Sleep (S3)	0.78	0.45	0.82	0.51	0.73	0.41		
Off (S5)	0.59	0.57	0.61	0.59	0.57	0.56		
Zero Power Mode (ErP)	0.21		0.22		0.2			

Heat Dissipation (Btu/hr)	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	25.181		29.889		23.986	
Windows short Idle (S0)	36.645		41.012		33.984	
Windows Busy Typ (S0)	308.342		339.562		301.041	
Windows Busy Max (S0)	324.515		350.685		320.25	
Sleep (S3)	2.661	1.535	2.798	1.74	2.491	1.399
Off (S5)	2.013	1.945	2.081	2.013	1.945	1.911
Zero Power Mode (ErP)	0.717		0.751		0.682	

Z2 Mini G5 Configuration #2	Processor Info	CPU I Core i7-10700 2.9GHz 8C65W
	Memory Info	16GB (2x 8GB) 2666 MHz DDR4 non-ECC
	Graphics Info	T1000 Graphics
	Disks/Optical/Floppy	1x SATA 256GB SSD
	Power Supply	280W

Energy Consumption (Watts)	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	15.23		15.63		15.01	
Windows short Idle (S0)	18.35		18.82		17.98	
Windows Busy Typ (S0)	109.47		109.88		107.36	
Windows Busy Max (S0)	140.9		142.95		138.56	
Sleep (S3)	1.13	0.73	1.15	0.78	1.1	0.69
Off (S5)	0.62	0.61	0.63	0.61	0.61	0.6
Zero Power Mode (ErP)	0.21		0.23		0.2	

Heat Dissipation (Btu/hr)	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	51.965		53.33		51.214	
Windows short Idle (S0)	62.61		64.214		61.348	
Windows Busy Typ (S0)	373.512		374.911		366.312	
Windows Busy Max (S0)	480.751		487.745		472.767	
Sleep (S3)	3.856	2.491	3.924	2.661	3.753	2.354
Off (S5)	2.115	2.081	2.15	2.081	2.081	2.047
Zero Power Mode (ErP)	0.717		0.785		0.682	

Z2 Mini G5 Configuration #3 ENERGY STAR CERTIFIED	Processor Info	CPU I Core i9-10900K 3.7GHz 10C125W
	Memory Info	64GB (2x 32GB) 2666 MHz DDR4 ECC
	Graphics Info	T1000 Graphics

System Technical Specifications

Disks/Optical/Floppy 1x SATA 512GB SSD
Power Supply 280W

Energy Consumption (Watts)	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	15.31		16.52		15.06	
Windows short Idle (S0)	18.74		19.04		18.32	
Windows Busy Typ (S0)	152.66		153.69		150.02	
Windows Busy Max (S0)	191.14		197.91		189.96	
Sleep (S3)	1.94	1.5	2.07	1.64	1.91	1.45
Off (S5)	0.62	0.6	0.63	0.61	0.61	0.6
Zero Power Mode (ErP)	0.23		0.24		0.22	

Heat Dissipation (Btu/hr)

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Enabled	LAN Disabled	LAN Enabled
Windows long Idle (S0)	52.238		56.366		51.385	
Windows short Idle (S0)	63.941		64.964		62.508	
Windows Busy Typ (S0)	520.876		524.39		511.868	
Windows Busy Max (S0)	652.17		675.269		648.144	
Sleep (S3)	6.619	5.118	7.063	5.596	6.517	4.947
Off (S5)	2.115	2.047	2.15	2.081	2.081	2.047
Zero Power Mode (ErP)	0.785		0.819		0.751	

Z2 Mini G5 Configuration #4

ENERGY STAR CERTIFIED

Processor Info CPU Xeon W-1250 3.3GHz 6C80W
Memory Info 16GB (2x 8GB) 2666 MHz DDR4 ECC
Graphics Info T2000 Graphics
Disks/Optical/Floppy 1x SATA 1TB SSD Z Turbo
Power Supply 280W

Energy Consumption (Watts)	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows long Idle (S0)	15.48		15.94		15.25	
Windows short Idle (S0)	19.47		19.5		19.13	
Windows Busy Typ (S0)	120.03		123.49		118.69	
Windows Busy Max (S0)	175.99		176.23		172.33	
Sleep (S3)	1.21	1.09	1.23	1.11	1.18	1.06
Off (S5)	0.64	0.63	0.66	0.64	0.6	0.59
Zero Power Mode (ErP)	0.22		0.24		0.21	

Heat Dissipation (Btu/hr)

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Enabled	LAN Disabled	LAN Enabled
Windows long Idle (S0)	52.818		54.387		52.033	
Windows short Idle (S0)	66.432		66.534		65.272	
Windows Busy Typ (S0)	409.542		421.348		404.97	
Windows Busy Max (S0)	600.478		601.297		587.99	
Sleep (S3)	4.129	3.719	4.197	3.787	4.026	3.617
Off (S5)	2.184	2.15	2.252	2.184	2.047	2.013
Zero Power Mode (ErP)	0.751		0.819		0.717	

System Technical Specifications

Declared Noise Emissions

System Configuration (Entry level)	Processor Info	W-1250P COMET LAKE WS P-1 6c LGA 125W WE1P 6(f)+2 vPro™ QSS / W-1250P COMET LAKE WS Q-0 6c LGA 4.1 GHz 125W QULG vPro™ Supplemental QS	
	Memory Info	Hynix (TG) 8GB 3200 DDR4 SODIMM ECC x2	
	Graphics Info	T2000	
	Disks/Optical/Floppy	SSD Z Turbo Drive 256GB 2280 PCIe NVMe Self Encrypted OPAL2 Three Layer Cell SS	
	Power Supply	280W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	SSD 512GB M.2 2280 PCIe NVMe Three Layer Cell 3rd	
System Configuration (Mid-level)	Processor Info	W-1290 COMET LAKE WS P-1 10c LGA 80W WE3 vPro™ QSK QS / W-1290 COMET LAKE WS Q-0 10c LGA 3.2 GHz 80W QUTJ vPro™ Supplemental QS	
	Memory Info	Samsung (TH) 8GB 3200 DDR4 SODIMM ECC x1	
	Graphics Info	T1000	
	Disks/Optical/Floppy	NA	
	Power Supply	280W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	HDD 500GB 7200RPM SATA SFF Self Encrypted Drive OPAL2	
System Configuration (High-end)	Processor Info	I5-10400 COMET LAKE G-0 6c LGA 65W MS0 QS	
	Memory Info	Hynix (TG) 8GB 3200 DDR4 SODIMM ECC x1	
	Graphics Info	Intel UHD Graphics	
	Disks/Optical/Floppy	SSD Z Turbo Drive 512GB 2280 Three Layer Cell 2nd	
	Power Supply	280W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	HDD 1TB 7200RPM 7mm SATA 2.5in	
System Configuration (Mid-level)	Processor Info	I3-10320 COMET LAKE G-0 6c LGA 65W T3 4(f)+2 QS	
	Memory Info	Micron (TF) 8GB 3200 DDR4 SODIMM ECC x2	
	Graphics Info	Intel UHD Graphics	
	Disks/Optical/Floppy	SSD Z Turbo Drive 512GB 2280 Three Layer Cell 2nd	
	Power Supply	180W	

System Technical Specifications

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	HDD 1TB 7200RPM 7mm SATA 2.5in	
System Configuration (High-end)	Processor Info	I3-10100 COMET LAKE G-0 6c LGA 65W T1 4(f)+2 QS	
	Memory Info	Micron (TF) 8GB 3200 DDR4 SODIMM ECC x2	
	Graphics Info	Intel UHD Graphics	
	Disks/Optical/Floppy	ZTRB HP Z Turbo Drive QX310 256GB SSD	
	Power Supply	180W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	HDD 1TB 7200RPM 7mm SATA 2.5in	
System Configuration (Mid-level)	Processor Info	I9-10900 COMET LAKE P-1 10c LGA 65W P2 vPro™ QS	
	Memory Info	Micron (TF) 4GB (1x4GB) 3200 DDR4 SODIMM NECC x2	
	Graphics Info	Intel UHD Graphics	
	Disks/Optical/Floppy	ZTRB HP Z Turbo Drive QX310 256GB SSD	
	Power Supply	180W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	ZTRB HP Z Turbo Drive QX310 256GB SSD	
System Configuration (High-end)	Processor Info	I5-10500 COMET LAKE G-0 6c LGA 65W MS1 vPro™ QS	
	Memory Info	Samsung (TH) 4GB (1x4GB) 3200 DDR4 SODIMM NECC x2	
	Graphics Info	Intel UHD Graphics	
	Disks/Optical/Floppy	SSD Z Turbo Drive 512GB 2280 PCIe NVMe Self Encrypted OPAL2 Three Layer Cell SS	
	Power Supply	180W	
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	TBD	TBD
	Hard drive Operating (random reads)	HDD 1TB 7200RPM 7mm SATA 2.5in	

Environmental Requirements

Temperature

Operating: 5° to 35° C (40° to 95° F)
 Non-operating: -40° to 60° C (-40° to 140° F)
 Maximum rate of change: 10°C/hr

Humidity

Operating: 10% to 85% RH, non-condensing, 35° C maximum wet bulb
 Non-operating: 10% to 90% RH, non-condensing, 35° C maximum wet bulb

System Technical Specifications

Maximum Altitude	Operating (with Rotational Hard Drives): 3,048 m (10,000 feet) Operating (with only Solid-State Drives): 5,000 m (16,404 feet) Non-operating: 12,192 m (40,000 feet) Maximum operating temperature is reduced as altitude increases. See Cooling for details.
Dynamic	Shock Operating: ½-sine: 40g, 2-3ms (~62 cm/sec) Non-operating: ½-sine: 160 cm/s, 2-3ms (~105g) square: 422 cm/s, 20g Vibration Operating random: 0.5g (rms), 5-300 Hz, up to 0.0025g ² /Hz Non-operating random: 2.0g (rms), 5-500 Hz, up to 0.0150 g ² /Hz
Cooling	Above 1524 m (5,000 feet) altitude, the maximum operating temperature is reduced by 1° C (1.8° F) for every 305 m (1,000 feet) increase in elevation, up to 3048 m (10,000 feet)

System Technical Specifications

Physical Security and Serviceability

Access Panel	Tool-less Has to remove Top panel before Bottom panel be removed.
Optical Drive	No
Hard Drives	HDD cage requires the use of a screwdriver to remove the HDD
Expansion Cards	M.2 module requires a screwdriver to service and replace. An option card requires a screwdriver to service and replace.
Processor Socket	Tool-less, except for the processor heatsink
Blue User Touch Points	Yes, on internal chassis mechanisms
Color-coordinated Cables and Connectors	Yes
Memory	Tool-less
System Board	Screw-In
Dual Color Power and HD LED on Front of Computer	The Power LED is on the front of the system, but the HDD LED is located on the Rear of the system
Restore CD/DVD Set	Consists of an operating system DVD (OSDVD) and a driver DVD (DRDVD). OSDVD restores the original operating system. DRDVD will provide all drivers for the system. The DRDVD may also contain applications that originally shipped with the system for optional installation. Applications can also be obtained from HP.com. OSDVD and DRDVD are orderable with the system and available from HP Support.
Dual Function Front Power Switch	Yes, causes a fail-safe power off when held for 4 seconds (default) or 15 seconds (can be configured by F10 BIOS setup\Advanced\System Options\Power button override)
Padlock Support	No
Cable Lock Support	Yes, Kensington Cable Lock (optional): Locks top cover from being opened and secures chassis to furniture to prevent theft 3 mm x 7 mm slot at rear of system
Universal Chassis Clamp Lock Support	No
Solenoid Lock and Hood Sensor	Only Hood Sensor(optional)
Rear Port Control Cover	No
Serial, USB, Audio, Network, Enable/Disable Port Control	Yes, enables or disables serial, USB, audio, and network ports (parallel port is not supported on the Z2 Mini G5)
Power-On Password	No
3.3V Aux Power LED on System PCA	No
NIC LEDs (integrated) (Green & Amber)	Yes
CPUs and Heatsinks	A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less

System Technical Specifications

Power Supply Diagnostic LED	Yes; this is located on the Rear of the chassis and combined with the HDD LED. When the PSU adapter is plugged in, and the unit is powered off, the Power OK LED will glow.
Front Power Button	Yes
Front Power LED	Yes, white (normal), red (fault)
Front Hard Drive Activity LED	HDD LED is located on the Rear of the chassis
Front ODD Activity LED	No
Internal Speaker	Yes
Cooling Solution	Air cooled forced convection
Power Supply Fans	No
Memory Heatsink Fan	No
Access Panel Key Lock	The Kensington lock slot on the chassis serves this purpose
Integrated Chassis Handles	No
Power Supply Flash ROM	No Yes
Diagnostic Power Switch LED on board	Yes
Clear CMOS Button	Yes
CMOS Battery Holder	Yes
DIMM Connectors	Yes
BIOS	
BIOS 32-bit Services	BIOS supports 64-bit Operating systems.
PCI 3.0 Support	Full BIOS support for PCI Express through industry standard interfaces.
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0.
BBS	BIOS Boot Specification v1.01.
WMI Support	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications.
BIOS Boot Spec 1.01+	Provides more control over how and from what devices the workstation will boot.
BIOS Power On	Users can define a specific date and time for the system to power on.
ROM Based Computer Setup Utility (F10)	Review and customize system configuration settings controlled by the BIOS.
System/Emergency ROM Flash Recovery with Video	Recovers system BIOS in corrupted Flash ROM.

System Technical Specifications

Replicated Setup	Saves BIOS settings to USB flash device in human readable file (HpSetup.txt). BiosConfigurationUtility.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup).
SMBIOS	System Management BIOS 3.2, for system management information.
Boot Control	Disables the ability to boot from removable media on supported devices.
Memory Change Alert	Alerts management console if memory is removed or changed.
Thermal Alert	Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none"> • NORMAL - normal temperature ranges. • ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown. • SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs.
Remote ROM Flash	Provides secure, fail-safe ROM image management from a central network console.
ACPI (Advanced Configuration and Power Management Interface)	Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 6.0 for full compatibility with 64-bit operating systems.
Ownership Tag	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
Remote Wakeup/Remote Shutdown	System administrators can power on, restart, and power off a client computer from a remote location.
Instantly Available PC (Suspend to RAM - ACPI sleep state S3)	Allows for very low power consumption with quick resume time.
Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)	Allows a new or existing system to boot over the network and download software, including the operating system.
ROM revision levels	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS and WMI) so that management SW applications can use and report this information.
System board revision level	Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified.
Start-up Diagnostics (Power-on Self-Test)	Assesses system health at boot time with selectable levels of testing.
Auto Setup when new hardware installed	System automatically detects addition of new hardware.
Keyboard-less Operation	The system can be booted without a keyboard.
Localized ROM Setup	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 14 languages with local keyboard mappings.
Asset Tag	The user or MIS to set a unique tag string in non-volatile memory.
Per-slot Control	Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually.
Adaptive Cooling	Control parameters are set according to detected hardware configuration for optimal acoustics.
Pre-boot Diagnostics	(Pre-video) critical errors are reported via beeps and blinks on the power LED.
Industry Standard UEFI Specification Revision	2.7
ACPI	Advanced Configuration and Power Management Interface, Version 6.0
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
CD Boot	"El Torito" Bootable CD-ROM Format Specification Version 1.0
EDD	Enhanced Disk Drive Specification Version 1.1 BIOS Enhanced Disk Drive Specification Version 3.0

System Technical Specifications

EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0
PCI	PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0, Draft .7
PCI Express	PCI Express Base Specification, Revision 2.0 PCI Express Base Specification, Revision 3.0
SATA	Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Serial ATA Specification, Revision 2.5 Serial ATA 6 Gb/s: Serial ATA Specification, Revision 3.0
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
TPM	Trusted Computing Group TPM Specification Version 2.0 (Infineon SLB 9670). Common Criteria EAL4+ certified. FIPS 140-2 Certification TCG TPM Certified products list: http://www.trustedcomputinggroup.org/certification/tpm-certified-products/
UHCI	Universal Host Controller Interface Design Guide, Revision 1.1
USB	Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification Universal Serial Bus Revision 3.1 Specification
SMBIOS	System Management BIOS Reference Specification, Version 3.2 External BIOS simulator found at: http://csrmsl.itcs.hp.com/

Social and Environmental Responsibility

Eco-Label Certifications & Declarations This product is low halogen except for power cords, cables and peripherals. Service parts obtained after purchase may not be Low Halogen.

- ENERGY STAR® (energy-saving features available on selected configurations –Windows® only)
- US Federal Energy Management Program (FEMP)
- China Energy Conservation Program (CECP)
- IT ECO declaration

Batteries The battery in this product complies with EU Directive 2006/66/EC
Battery size: CR2032 (coin cell)
Battery type: Lithium Metal

The battery in this product does not contain:

- Mercury greater than 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 40ppm by weight

Restricted Material Usage This product meets the material restrictions specified in HP's General Specification for the Environment. <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>
HP Inc. is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis.

End-of-Life Management and Recycling HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. This product is greater than 90% recyclable by weight when properly disposed of at end of life.

System Technical Specifications

HP Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:
Living Progress Report <http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications
<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:
<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

Additional Information

- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product is >90% recycle-able when properly disposed of at end of life
- EPEAT®2019 Gold registered in the United States*

*Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit www.epeat.net for more information.

Packaging

HP Workstation product packaging meets the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/society/gen_specifications.html

- Does not contain restricted substances listed in HP Standard 011-1 General Specification for the Environment
- Does not contain ozone-depleting substances (ODS)
- Does not contain heavy metals (lead, mercury, cadmium or hexavalent chromium) in excess of 100 ppm sum total for all heavy metals listed
- Maximizes the use of post-consumer recycled content materials in packaging materials
- All packaging material is recyclable
- All packaging material is designed for ease of disassembly
- Reduced size and weight of packages to improve transportation fuel efficiency
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards formatting

Packaging Materials

Internal

Cushions made from fabricated recycled expanded-polyethylene (EPE) or recycled expanded-polypropylene (EPP). May also be made from recycled molded paper-pulp (MPP).

External

Carton made from corrugated fiberboard with at least 35% recycled content.

System Technical Specifications

Manageability

Remote Manageability Software Solutions

The HP Z2 G5 Workstation is supported on the following remote manageability software consoles:

- LANDesk Management Suite (HP recommended solution)
- Microsoft System Center Configuration Manager

For questions or support for manageability needs, please visit

<http://www.hp.com/go/clientmanagement>

HP Image Assistant

System Software Manager

Visit: <http://ftp.hp.com/pub/caps-softpaq/cmit/HPIA.html>

For questions or support for SSM, please visit: <http://www.hp.com/go/ssm>

Stable & Consistent Offerings

As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section.

HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers—no special programs, no additional cost, no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

Processors	Product #	Offering
		Intel Core i3-10100 3.6 4C 65W processor
		Intel Core i5-10500 3.1 6C 65W processor
		Intel Core i5-10600 3.3 6C 65W processor
		Intel Core i7-10700 2.9 8C 65W processor
		Intel Xeon W-1250 3.3 6C 80W processor
		Intel Xeon W-1250P 4.1 6C 125W processor

Hard Drives	Product #	Offering
		1TB 7200RPM 9.5mm SATA 2.5 HDD

Graphics	Product #	Offering
		AMD Radeon™ Pro WX 3200 4GB

Technical Specifications - Processors

10th Generation Intel Core Processors

Intel® Core™ i9-10900K Processor

Intel® Core™ i9-10900 Processor

Intel® Core™ i9-10900F Processor¹

Intel® Core™ i7-10700K Processor

Intel® Core™ i7-10700 processor

Intel® Core™ i5-10600K processor

Intel® Core™ i5-10600 processor

Intel® Core™ i5-10500 processor

Intel® Core™ i5-10400 processor

Intel® Core™ i5-10400F Processor¹

Intel® Core™ i3-10320 processor¹

Intel® Core™ i3-10300 processor¹

Intel® Core™ i3-10100 processor

Intel Xeon W Processors

Intel® Xeon® W-1290P processor

Intel® Xeon® W-1290 processor¹

Intel® Xeon® W-1270P processor¹

Intel® Xeon® W-1270 processor

Intel® Xeon® W-1250P processor

Intel® Xeon® W-1250 processor

NOTE 1: Available in Q4, 2020

Technical Specifications - Hard Drives

SATA Hard Drives for HP Workstations	500GB SATA 7200 rpm 6Gb/s 2.5" HDD	Capacity	500GB
		Protocol	SATA
		Form Factor	SFF (2.5")
		Controller	AHCI
		Rated for 24/7/365 operation	NO
		Physical Size (Height)	0.28 in; .7 cm
		Physical Size (Width)	2.75 in; 6.99 cm
		Media Diameter	2.5 in; 6.36 cm
		Interface	Serial ATA (6Gb/s), NCQ enabled
		Synchronous Transfer Rate (Maximum)	Up to 600MB/s*
		Operating Temperature	32° to 140° F (5° to 55° C)
		<i>*Actual performance may vary.</i>	
		1TB SATA 7200 rpm 6Gb/s 2.5" HDD	Capacity
		Protocol	SATA
		Form Factor	SFF (2.5")
		Controller	AHCI
		Rated for 24/7/365 operation	NO
		Physical Size (Height)	0.28 in; .7 cm
		Physical Size (Width)	2.75 in; 6.99 cm
		Media Diameter	2.5 in; 6.36 cm
		Interface	Serial ATA (6Gb/s), NCQ enabled
		Synchronous Transfer Rate (Maximum)	Up to 600MB/s*
		<i>*Actual performance may vary.</i>	
	2TB SATA 7200 rpm 6Gb/s 2.5" HDD	Capacity	2TB
		Protocol	SATA
		Form Factor	SFF (2.5")
		Controller	AHCI
		Physical Size (Height)	0.28 in; .7 cm
		Physical Size (Width)	2.75 in; 6.99 cm
		Media Diameter	2.5 in; 6.36 cm
		Operating Temperature	32° to 140° F (5° to 55° C)
		<i>*Actual performance may vary.</i>	
	500GB SATA 7.2K SED 2.5" HDD	Capacity	500GB
		Protocol	SATA
		Form Factor	2.5"
		Physical Size (Height)	0.275 in; 0.7 cm
		Physical Size (Width)	2.5 in; 6.36 cm
		Media Diameter	2.75 in; 6.99 cm

Technical Specifications - Hard Drives

Interface	Serial ATA (6Gb/s), NCQ enabled	
Synchronous Transfer Rate (Maximum)	Up to 600MB/s*	
Buffer	64MB	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1ms*
	Average	4.2ms*
	Full Stroke	25ms (Typical)*
Rotational Speed	7,200 rpm	
Operating Temperature	32° to 131° F (0° to 60° C)	
Self-Encrypting Drive Support	Yes	

*Actual performance may vary.

HP 256GB SATA 6Gb/s SSD

Capacity	256GB
Protocol	SATA
Form Factor	2.5"
Physical Size (Height)	0.28 in; 0.7 cm
Physical Size (Width)	Physical Size
Synchronous Transfer Rate (Maximum)	Up to 550MB/s (Sequential Read)*
Operating Temperature	32° to 158° F (0° to 70° C)

*Actual performance may vary.

PCIe SSDs for HP Workstations

HP Z Turbo Drv 256GB TLC PCIe SSD (Z2G5)

Capacity	256GB	
Protocol	PCIe	
Form Factor	M.2 in native slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	75TBW (TB Written)	
Reliability (MTBF)	1.5M hours	
Interface	PCI Express 3.0 x4	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	2800 MB/s*
	Sequential Write	1100MB/s*
	Random Read	250K IOPS*
	Random Write	180K IOPS*

*Actual performance may vary.

HP Z Turbo Drv 512GB TLC PCIe SSD (Z2G5)

Capacity	512GB
Protocol	PCIe
Form Factor	M.2 in native slot on motherboard
Controller	NVMe
NAND Type	3D TLC

Technical Specifications - Hard Drives

Endurance	150TBW (TB Written)	
Reliability (MTBF)	1.5M hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	2800 MB/s*
	Sequential Write	1600MB/s*
	Random Read	260K IOPS*
	Random Write	260K IOPS*

*Actual performance may vary.

HP Z Turbo Drv 1TB TLC PCIe SSD (Z2G5)

Capacity	1TB	
Protocol	PCIe	
Form Factor	M.2 in native slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	300TBW (TB Written)	
Reliability (MTBF)	1.5M hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	3000 MB/s*
	Sequential Write	1700MB/s*
	Random Read	360K IOPS*
	Random Write	330K IOPS*

*Actual performance may vary.

HP Z Turbo Drv 2TB TLC PCIe SSD (Z2G5)

Capacity	2TB	
Protocol	PCIe	
Form Factor	M.2 in native Slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	600TBW (TB Written)	
Reliability (MTBF)	1.5M hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	3000 MB/s*
	Sequential Write	2100MB/s*
	Random Read	320K IOPS*
	Random Write	265K IOPS*

*Actual performance may vary.

HP Z Turbo Drv 256GB TLC PCIe SED OPAL2 (Z2G5)

Capacity	256GB	
Protocol	PCIe	
Form Factor	M.2 in native Slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	

Technical Specifications - Hard Drives

Endurance	75TBW (TB Written)	
Reliability (MTBF)	1.5M Hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	2800MB/s*
	Sequential Write	1100MB/s*
	Random Read	250K IOPS*
	Random Write	180K IOPS*
Self-Encrypting Drive Support	OPAL2	

*Actual performance may vary.

HP Z Turbo Drv 512GB TLC PCIe SED OPAL2 (Z2G5)

Capacity	512GB	
Protocol	PCIe	
Form Factor	M.2 in native Slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	150TBW (TB Written)	
Reliability (MTBF)	1.5M Hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	2800MB/s*
	Sequential Write	1600MB/s*
	Random Read	260K IOPS*
	Random Write	260K IOPS*
Self-Encrypting Drive Support	OPAL2	

*Actual performance may vary.

HP Z Turbo Drv 1TB TLC PCIe SED OPAL2 (Z2G5)

Capacity	1TB	
Protocol	PCIe	
Form Factor	M.2 in native Slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	300TBW (TB Written)	
Reliability (MTBF)	1.5M Hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	3000MB/s*
	Sequential Write	1700MB/s*
	Random Read	360K IOPS*
	Random Write	330K IOPS*
Self-Encrypting Drive Support	OPAL2	

*Actual performance may vary.

Technical Specifications - Hard Drives

**HP Z Turbo Drv 2TB
TLC PCIe SED
OPAL2 (Z2G5)**

Capacity	2TB	
Protocol	PCIe	
Form Factor	M.2 in native Slot on motherboard	
Controller	NVMe	
NAND Type	3D TLC	
Endurance	600TBW (TB Written)	
Reliability (MTBF)	1.5M Hours	
Interface	PCI Express 3.0 x4 electrical	
Operating Temperature	32° to 158° F (0° to 70° C)	
Performance	Sequential Read	3000MB/s*
	Sequential Write	2100MB/s*
	Random Read	320K IOPS*
	Random Write	265K IOPS*
Self-Encrypting Drive Support	OPAL2	

*Actual performance may vary.

Technical Specifications - Graphics

AMD Radeon™ Pro WX 3200 4GB Graphics	Form Factor	Mobile PCI Express Custom Module
	Power	35W
	Bus Type	PCI Express 3.0 x8
	Memory	4GB GDDR5
	Connectors	3x DisplayPort™ 1.4 – HDR ready connectors with HBR3 and MST support.
	Maximum Resolution	4096x2160 x 24 bpp @ 60Hz
	Supported Graphics APIs	DirectX®12 OpenGL® 4.5 OpenCL™ 2.0 Vulkan™ 1.0
	Available Graphics Drivers	Windows 10 64-bit Linux® 64-bit (selected Enterprise distributions)
		HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html

Nvidia® Quadro® P620 4GB Graphics	Form Factor	Mobile PCI Express Custom Module
	Power	35W
	Bus Type	PCI Express 3.0 x16
	Memory	4GB GDDR5
	Connectors	3x DisplayPort™ 1.2 – HDR ready connectors with HBR2 and MST support.
	Maximum Resolution	4096x2160 x 24 bpp @ 60Hz
	Supported Graphics APIs	DirectX®12 OpenGL® 4.5 OpenCL™ 2.0 Vulkan™ 1.0
	Available Graphics Drivers	Windows 10 64-bit Linux® 64-bit (selected Enterprise distributions)
		HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html

Nvidia® Quadro® T1000 4GB Graphics	Form Factor	Mobile PCI Express Custom Module
	Power	50W
	Bus Type	PCI Express 3.0 x16
	Memory	4GB GDDR6
	Connectors	3x DisplayPort™ 1.4 – HDR ready connectors with HBR3 and MST support.
	Maximum Resolution	5120 x 3200 @ 60Hz
	Supported Graphics APIs	DirectX®12 OpenGL® 4.5 OpenCL™ 2.0 Vulkan™ 1.0

Technical Specifications - Graphics

Available Graphics Drivers

Windows 10 64-bit
Linux® 64-bit (selected Enterprise distributions)

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

**Nvidia® Quadro® T2000
4GB Graphics**

Form Factor

Mobile PCI Express Custom Module

Power

60W

Bus Type

PCI Express 3.0 x16

Memory

4GB GDDR6

Connectors

3x DisplayPort™ 1.4 – HDR ready connectors with HBR3 and MST support.

Maximum Resolution

5120 x 3200 @ 60Hz

Supported Graphics APIs

DirectX®12
OpenGL® 4.5
OpenCL™ 2.0
Vulkan™ 1.0

Available Graphics Drivers

Windows 10 64-bit
Linux® 64-bit (selected Enterprise distributions)

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

**Nvidia® Quadro® RTX
3000 6GB Graphics**

Form Factor

Mobile PCI Express Custom Module

Power

60W

Bus Type

PCI Express 3.0 x16

Memory

6GB GDDR6

Connectors

3x DisplayPort™ 1.4 – HDR ready connectors with HBR3 and MST support.

Maximum Resolution

5120 x 3200 @ 60Hz*

**Requires 2 DisplayPorts™ to be plugged into a 5K monitor.*

Supported Graphics APIs

DirectX®12
OpenGL® 4.5
OpenCL™ 2.0
Vulkan™ 1.0

Available Graphics Drivers

Windows 10 64-bit
Linux® 64-bit (selected Enterprise distributions)

HP qualified drivers may be preloaded or available from the HP support Web site:
<http://welcome.hp.com/country/us/en/support.html>

Technical Specifications - Networking and Communications

Integrated Intel® I219LM PCIe GbE Controller (Intel® vPro™ with Intel® AMT 12.0)	Connector	RJ-45
	Controller	Intel® I219LM GbE platform LAN connect networking controller
	Memory	3 KB Tx and 3KB Rx FIFO packet buffer memory
	Data Rates Supported	10/100/1000 Mbps
	Compliance	802.1as/1588, 802.1p, 802.1Q, 802.3, 802.3ab, 802.3az, 802.3i, 802.3u, 802.3z
	Bus Architecture	PCI Express and SMBus
	Data Transfer Mode	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)
	Power Requirement	Requires 3.3V (integrated regulators for core Vdc)
	Boot ROM Support	Yes
	Network Transfer Mode	Full-duplex; Half-duplex (not supported for the 1000BASE-T transceiver)
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
Management Capabilities	vPro™, WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, ACPI, Advanced cable diagnostic, loopback modes, AMT 12.0 support, Circuit Breaker, VLAN, Multicast Listener Discovery (MLD)	

Intel® 9560 Wireless LAN (802.11ac) and Bluetooth 5 Module	Connector	M.2 (Supports 2230 form factor; E Key) Motherboard Interface
	Controller	Intel® Dual Band Wireless-AC 9560
	Compliance	Wireless LAN: IEEE 802.11abgn, 802.11ac, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w, CCX 4.x/CCX Lite, WMM, WPA, WPA2, APS, WPS 2.0, Protected Management Frames Bluetooth®: Dual Mode Bluetooth® 2.1, 2.1+EDR, 3.0, 4.0, BLE, 4.2, and 5
	Bus Architecture	PCI Express Gen3 x1 and USB 2.0
	Power Requirement	Requires 3.3V; 1.65W TDP
Management Capabilities	Wake on WLAN (in all sleep states, excluding Max Power Savings mode), WFA Management Frame Protection (802.11w), vPro™/WiAMT Not Currently Supported, F10 BIOS Menu option to disable/enable WLAN and Bluetooth® radios, supports seamless roaming between 802.11 wireless access points	
Throughput	Max PHY throughput 1.73 Gbps (802.11ac) for WLAN	

Allied Telesis 1GbE LC Fiber 2pc Module	Network Interface(s)	1 LC Fiber Connection
	System Interface	PCI Express Gen1.1x1 (via WLAN M.2 interface)
	Network Cable	1GbE over Multimode LC Fiber. Distance is dependent upon network cable: OM1 50/125um 500 MHz:km 550m OM2 62.5/125um 200 MHz:km 275m OM2 62.5/125um 160MHz:km 220m

Technical Specifications - Networking and Communications

Data Rates Supported	1 Gbps
LED Indicators	Link/Activity LED (Green): Off = No Link, Solid = Link, Blinking = Activity
Controller	Broadcom BCM57762
Compliance	IEE 802.3z Base1000SX 802.3x (Ethernet Flow Control) 802.1Q (VLANs) 802.1P (Quality of Service) FCC B (USA) CE (European Union) ICES-003 B (Canada) BSMI (Taiwan) VCCI (Japan) KCC (Korea) CTICK (Australia/New Zealand) UL (Safety) RoHS (Restricted or Hazardous Substances)
Power Requirement	2W (Typical)
Operating Temperature	32° to 122° F (0° to 50° C)
Physical Dimensions (LxW)	LC Fiber Board: 37mm x 45mm x 13mm (WxLxH, including connector) Cable: 200mm M.2 Board: 22mm x 30mm x 1.75mm (WxLxH)
Kit Contents	LC fiber board, M.2 board, connecting cable, and 2 screws for attaching the LC fiber board to the motherboard Product Warranty statement and the Installation Guide.

Technical Specifications – Miscellaneous Features

MISCELLANEOUS FEATURES

Management Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- Intel® Wired for Management support; industry wide initiative to make Intel® architecture based PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

Serviceability Features

- Dual colored power LED on front of computer to indicate either normal or fault condition
- Diagnostic LED Explanation Table:
 - Power LED will blink red 2 to 5 times, then blink white 2 or more times, then repeat (with beep tones for each blink initially):
 - 2 red + 2 white User must provide file for BIOS recovery (USB storage typically) + 2 white User must provide file for BIOS recovery (USB storage typically) + 2 white User must provide file for BIOS recovery (USB storage typically)
 - 2 red + 3 white User must enter a key sequence to proceed with recovery by policy + 3 white User must enter a key sequence to proceed with recovery by policy + 3 white User must enter a key sequence to proceed with recovery by policy
 - 2 red + 4 white BIOS recovery is in progress + 4 white BIOS recovery is in progress + 4 white BIOS recovery is in progress
 - 3 red + 2 white Memory could not be initialized + 2 white Memory could not be initialized + 2 white Memory could not be initialized
 - 3 red + 3 white Graphics adaptor could not be found + 3 white Graphics adaptor could not be found + 3 white Graphics adaptor could not be found
 - 3 red + 4 white Power supply failure / not connected + 4 white Power supply failure / not connected + 4 white Power supply failure / not connected
 - 3 red + 5 white Processor not installed + 5 white Processor not installed + 5 white Processor not installed
 - 3 red + 6 white Current processor does not support an enabled feature + 6 white Current processor does not support an enabled feature + 6 white Current processor does not support an enabled feature
 - 4 red + 2 white Processor has exceeded its temperature threshold / system thermal shutdown + 2 white Processor has exceeded its temperature threshold / system thermal shutdown + 2 white Processor has exceeded its temperature threshold / system thermal shutdown
 - 4 red + 3 white System internal temperature has exceeded its threshold + 3 white System internal temperature has exceeded its threshold + 3 white System internal temperature has exceeded its threshold
 - 5 red + 2 white System controller firmware is not valid
 - 5 red + 3 white System controller detected BIOS is not executing
 - 5 red + 4 white BIOS could not complete initialization / PCA failure
 - 5 red + 5 white System controller rebooted the system after a health or recovery timer triggered rebooted the system after a health or recovery timer triggered rebooted the system after a health or recovery timer triggered
- HP PC Hardware Diagnostics UEFI:
 - This utility enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support
- System/Emergency ROM
- Flash ROM
- CMOS Battery Holder for easy replacement
- Flash Recovery with Video Configuration Record Software
- Processor ZIF Socket for easy Upgrade
- Over-Temp Warning on Screen (Requires IM Agents)

Technical Specifications – Miscellaneous Features

- Clear Password Jumper
- DIMM Connectors for easy Upgrade
- Clear CMOS Button
- NIC LEDs (integrated) (Green & Amber)
- Color coordinated cables and connectors
- Tool-less Hood Removal
- Front power switch
- System memory can be upgraded without removing the system board or any internal components
- Tool-less Hard Drive, CD & Diskette Removal
- Green Pull Tabs, and Quick Release Latches for easy Identification

Summary of Changes

Date of change:	Version History:		Description of change:
	From v1 to v2		

© 2020 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Intel Core, Pentium, Thunderbolt, vPro and Xeon are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ENERGY STAR® is a registered trademark owned by the U.S. Environmental Protection Agency. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. NVIDIA®, Quadro and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Red Hat® is a registered trademark of Red Hat, Inc. in the United States and other countries. Bluetooth is a trademark of its proprietor used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.